

BOOT SCOOTER SUPALITE

THE ULTIMATE PORTABLE TRAVEL SCOOTER!

UP TO 8 KG LIGHTER THAN COMPARABLE TRAVEL SCOOTERS



Aluminium chassis construction



Lithium-ion battery pack





Easy-to-grip tiller handles

Exclusively Distributed by:



Every day is a new adventure with the **Aspire Boot Scooter Supalite**, an exceptionally stable and manoeuvrable 4-wheel travel scooter. Benefiting from a class-leading, ultralightweight design and a maximum speed up to 6.5 km/h, the Boot Scooter Supalite keeps up with your active life!



SPECIFICATIONS

BOOT SCOOTER SUPALITE

Model Name	Boot Scooter Supalite (4-wheel)
Weight Capacity	120 kg (265 lbs.)
Maximum Speed ¹	6.5 km/h (4.1 mph)
Ground Clearance ²	3.2 cm (1.25") at motor
Turning Radius ²	138.5 cm (54.5")
Overall Length ²	102.2 cm (40.25")
Overall Width ²	49 cm (19.25")
Tyre Information	Solid (front and rear (20.3 cm (8"))
Seat-to-Deck Height	41.9 - 45.7 cm (16.5 - 18")
Seat Height	35.5 cm (14")
Overall Height	88.2 cm (34.75")
Total Unit Weight	34 kg (74.9 lbs.)
Heaviest Piece	Front section (10.7 kg (23.5 lbs.))
Range Per Charge ^{1,4}	Up to 14.4 km (8.9 miles) at 120 kg (265 lbs.) Up to 18.5 km (11.5 miles) at 90.7 kg (200 lbs.)
Standard Seating	Type: Molded Plastic Weight: 7.5 kg (16.5 lbs.) Material: Black Vinyl Width: 43.2 cm (17") Depth: 43.2 cm (17")
Drive System	Rear-wheel drive, single motor, 24V DC motor
Dual Braking System	Regenerative and electromechanical
Battery Requirements ³	Single 24-volt, Lithium-ion, 12 Ah, Weight : 3.5 kg
Battery Charger	2 amp off-board charger

FEATURES

- Compact, foldable seat with armrests
- Easy-to-grip tiller adjustment knob
- Stable, front frame-mounted seat post
- A standard front basket provides storage
- Easy to transport at home, hotels, or airports



Disassembles into 6 lightweight pieces for lightweight transport and storage!



 Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tyre type, and tyre condition. This specification can be subject to a variance of +10%, -5%.

2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

 AGM, Gel-Cell, or Hybrid Gel (Hybrid Gel is defined as Nano Silica Gel Electrolyte with High Quality Glass Mat Separators) type required. See III. "Batteries and Charging."

 Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

NOTE: This product conforms to all applicable ANSI/RESNA, ISO 7176 series, AS/NZS 3695.2, and EN12184 standards. All specifications subject to change without notice. Exclusively Distributed by: initial content of the second second

> 1300 133 120 www.aidacare.com.au