

4-Wheel Stability with 3-Wheel Maneuverability

Pride









Get a 4-wheel scooter with a 3-wheel turning radius with the **Pride® Zero Turn** and Pride's patented, intelligent-turning, iTurn Technology[™]. Navigate tight corners and small spaces effortlessly with a 97.2 cm (38.25") turning radius. Illuminate your ride with bright LED lighting. Dual motors and CTS Suspension ensure a smooth and comfortable drive.

PRIDE[®] MOBILITY SCOOTERS LIVE YOUR BEST[®]



Specifications

Weight Capacity	136 kg (300 lbs.)
Maximum Speed ¹	Up to 6.4 km/h (4 mph)
Ground Clearance ²	3.3 cm (1.3") at motor
Turning Radius ²	97.2 cm (38.25″)
Overall Length ²	116.2 cm (45.75″)
Overall Width ²	50.8 (20")
Front Tyres	5 x 17.8 cm (2" x 7") solid
Rear Tyres	6.35 x 22.9 cm (2.5" x 9") solid
Range Per Charge ^{2,4}	Up to 16 km (10 miles)
Total Weight Without Batteries	54 kg (120 lbs.)
Heaviest Piece When Disassembled	21.8 kg (48 lbs.) (rear section)
Standard Seating	Type: Foldable, molded plastic Weight: 12 kg (27 lbs.) Material: Black vinyl Dimensions: Width: 43.2 cm (17") Depth: 43.2 cm (17")
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Electronic, regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle Size: (2) 22 AH Weight: Battery box 15 kg (32 lbs.) 6 kg each
Battery Charger	Off-board, 3.5 amp
Delta Tiller	Yes
Colours	Fire Pearl Sapphire Opal White Blue

Guality Endorsed Company 901 06:2000



Features

- First ever indoor 4-wheel scooter
- Charging port built into the tiller for easy charging
 Contemporary new rim design makes the
- Pride[®] Zero Turn Scooter look as good as it drives
- CTS Suspension for comfortable long range use
- Delta tiller, ergonomic wraparound handles enables easy-to-use left or right hand operation
- Dual motors for added traction in rough terrain
- Feather-touch disassembly permits simple frame separation with only one hand
- Front basket
- Full LED lighting package for safe operation Patented iTurn Technology™ provides 4-wheel
- stability with 3-wheel maneuverability
 Under seat storage comes standard
- USB charger built into the tiller for convenient charging of smart phones and portable devices
- Your choice of three contemporary, interchangeable colour shrouds

Accessories

- Pride stick holder
- Walker holder (must have Pride rear bag to attach) Oxygen tank holder (must have Pride rear
- bag to attach)
- Mobile phone holder
- Cup holder
 - Rear view mirror
 - Saddle bag

Tackle the tightest turns with the Pride Zero Turn Scooter

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- AGM or gel cell type required.
 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations
- based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

