



## Specifications

DRIVE WHEELS	Standard: 35.56 cm (14") flat free
CASTER WHEELS	Rear. 22.86 cm (9") flat free
ANTI-TIP WHEELS	Front: 10.16 cm (4") flat free
MAXIMUM SPEED <sup>1</sup>	Up to 9.6 km/h (6 mph)
GROUND CLEARANCE	6.7 cm (2.6") (motor pivot)
TURNING RADIUS <sup>2</sup>	62.25 cm (24.5")
OVERALL LENGTH <sup>2</sup>	101.4 cm (39.9")
BASE WIDTH	61.6 cm (24.2")
SEATING SIZES	
TRU-Balance® 3 Static Seat	Width: 30.5-56 cm (12-22") Depth: 30.5-56 cm (12-22")
TRU-Balance <sup>®</sup> 3 Power Tilt	Width: 30.5-56 cm (12-22") Depth: 30.5-56 cm (12-22")
TRU-Balance® 3 Lift & Tilt	Width: 30.5-56 cm (12-22") Depth: 30.5-56 cm (12-22")
SEAT-TO-FLOOR HEIGHTS <sup>9</sup>	
TRU-Balance® 3 Static Seat <sup>5</sup>	38.7-43.8 cm (15.25-17.25")
TRU-Balance® 3 Power Tilt <sup>5</sup>	44.5-49.5 cm (17.5-19.5")
TRU-Balance® 3 Lift & Tilt <sup>5</sup>	45-50 cm (17.75-19.75")
MANUAL RECLINE	Yes
BATTERY SIZE <sup>3</sup>	70 AH (2)
BATTERY WEIGHT 6	23.4 kg (51.5 lbs.) each
AVAILABLE ELECTRONICS 7	120A Q-Logic 3 EX
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	Two-pole, front-wheel drive
WEIGHT CAPACITY <sup>4</sup>	136 kg (300 lbs.)
BASE WEIGHT	63.5 kg (140 lbs.)

1) Speed varies with user weight, terrain type, battery charge, battery condition and tyre pressure.

- Without front riggings
   Battery capacity may change when adding power positioning systems.
   Weight capacity is dictated by the selection of seating.
- 5) All measurements +/- 3 mm (1/8") with 46 x 46 cm (18" x 18") seat, fixed towers, 136 kg (300 lbs.) weight capacity and solid tyres (add 10 mm (3/8") with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- 6) Battery weight may vary +/- 1.4 kg (3 lbs.) based on manufacturer.
  7) All Quantum Rehab® units can be ordered with specialty controls.
  8) Call for availability

- 9) Seat-to-floor heights are measured with the unit unloaded. Due to the 4Front's suspension system, seat-to-floor heights are approximately 6 mm (0.25") lower when the unit is loaded.







## Standard Features

- CASE (Castor Angle Sensor Encoder) technology
- Unmatched driving performance and ride quality
- Advanced stability for smooth obstacle transitions
- Superior, automotive-grade SRS (Smooth Ride . Suspension)
- Q-Logic 3 EX Advanced Drive Controls
- Quiet ride technology

## Options

- 25.4 cm (10") of power adjustable safe seat elevation at speeds of up to 5.1 km/h (3.2 mph)
- TRU-Balance<sup>®</sup> 3 Seating
- TRU-Comfort 2 Seating

## Colours



Red





Trilogy vent tray <sup>8</sup>

lights

Compact vent tray <sup>8</sup>

LED front and rear fender



in Black

Electric Blue

Corvette



Purple



AFY145 240419